



# TempTale® Ultra

## TempTale® Ultra Dry Ice Probe Monitor

### Validated, detachable probed TempTale® Ultra for monitoring dry ice shipments

The TempTale® Ultra Dry Ice Probe monitor is an ideal solution for monitoring in-transit and storage temperatures of biological samples (i.e., tissue, blood, etc.) and temperature-sensitive biomedical/pharmacological products that require very low temperatures to maintain their stability.

Probe options include 1 meter (3.3 foot) and 3 meter (10 foot) lengths, perfect for monitoring temperature close to product inside dry ice shippers or large dry ice freezers. The TempTale Ultra Dry Ice Probe monitor allows supply-chain partners (such as customs agents, third-party logistics (3PL) providers, distributors, and hospitals) to disconnect/reconnect the probe, to assess temperature data and alarm status without opening the carton (no disruption of temperature probe as it continues on its journey). For shipping lanes involving customs agents, this is a “must have” requirement (i.e., Saudi Arabia FDA Regulations).

The detachable probe enables receivers to read the LCD status immediately, thereby expediting decisions at the dock, no longer requiring the LCD to “warm-up” and display the alarm status. The TempTale Ultra Dry Ice Probe monitor is available in both Single Use, Single Use Overwrite, and Multi Use recording options.

---

### Features and Benefits

- External dry ice probe allows customers to record temperatures inside packaging and view key temperature indicators on the monitor's LCD outside of the package without opening the package.
- No longer will probes need to acclimate to the frozen environment each time the package is inspected or the monitor is downloaded. Temperature monitoring remains more stable now that the probe can remain next to the product inside the dry ice shipper, while the actual USB monitor remains on the outside for easy data downloading.
- Direct USB connection to PC—no proprietary reader or USB adapter needed to access data stored on monitor; PDF options are configurable: selectable time zones and languages enhance usability at international receiving sites.



TempTale Ultra Specifications	
<b>Monitoring Recording Options</b>	Single Use, Single-Use with User Programmable Overwrite, or Multiple Use
<b>Probe Temperature Measurement Range</b>	-90°C to + 30°C (-130°F to +86°F)
<b>Probe Sensor Accuracy Range</b>	±1.5°C from -90°C to +30°C (±2.7°F from -130°F to +86°F)
<b>Monitor Operating Range</b>	-30°C to + 70°C (-22°F to +158°F)
<b>Temperature Resolution</b>	0.1°C/F over full temperature measurement range
<b>Data Memory Type</b>	Non-volatile 16K Flash memory
<b>Data Storage Capacity</b>	16,000 data points (16K)
<b>Battery Life / Type</b>	12 months operating life / 3.6v lithium battery
<b>Data Sampling Interval</b>	Programmable from 30 seconds up to a maximum of 120 minutes
<b>Water Resistant Housing</b>	IP64 (with detachable probe connected to monitor)
<b>Start Up Delay</b>	0 minutes to 24 hours
<b>Programmable Alarms</b>	Alarm Mode Options <ul style="list-style-type: none"> <li>• High/Low</li> <li>• Multi-Alarm (up to six) – single temperature limit, temperature range, dual temperature range, MKT, duration</li> </ul>
<b>Alarm Delay Time Thresholds</b>	Single event (continuous) or cumulative
<b>LCD Indicators</b>	Started, start-up delay, running, stopped; Alarm status: OK (✓), Alarmed (✗); Trip summary data (average, minimum, maximum); Current temperature reading; Time remaining / time elapsed against alarm thresholds; PROBE and X flash when probe disconnects from monitor
<b>Cable Length Options</b>	1m and 3m
<b>Outer diameter of cable (typical)</b>	3.5mm
<b>Weight (typical)</b>	82.2 grams (2.9 oz) with 1m probe 119.0 grams (4.2 oz) with 3m probe
<b>Quality Assurance Certifications</b>	CE, EN/12830, RTCA – D0160G; 3-point NIST® traceable Certificate of Calibration
<b>Minimum System Requirements</b>	Windows® PC w/ Windows® 7 Pro (64-bit) or higher; Adobe® Reader 9.0 or higher
<b>Data Analysis and Cold Chain Continuous Improvement Software</b>	TempTale Manager® Desktop 8.0 or higher; ColdStream® Cold Chain Manager 1.8A or higher; ColdStream® Web 1.1
<b>Computer Interface</b>	USB 2.0, A-type plug

Sensitech Inc. is focused on delivering supply chain visibility solutions that track, monitor and protect products for global leaders in the food, life sciences, consumer goods, and industrial markets. Our solutions are focused in three key areas: quality and compliance, supply chain security, and logistics performance management. Quality and compliance solutions address temperature-sensitive, complex supply chains focused on delivering the highest quality possible, while our supply chain security solutions help to mitigate risks associated with theft, diversion and chain of custody. Sensitech's logistics performance solutions deliver origin-to-destination, real-time transparency to any in-transit journey. Sensitech Inc. is an ISO 9001:2008 company, headquartered in Beverly, Mass., with more than 35 sales, service and distribution locations around the world. Sensitech is a part of UTC Climate, Controls & Security, a unit of United Technologies Corp., a leading provider to the aerospace and building systems industries worldwide. Visit [www.sensitech.com](http://www.sensitech.com) for additional information. © 2017 Sensitech Inc. All Rights Reserved. Unless otherwise indicated, all trademarks and service marks are the property of Sensitech Inc. Microsoft, Windows, Windows XP, Windows Vista, and Internet Explorer are registered trademarks of Microsoft Corporation in the United States and other countries. Adobe is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. NIST is a registered trademark of The National Institute of Standards and Technology Agency of the United States Government.