



TempTale® Ultra

Probeless Dry Ice Monitor

Introducing the TempTale® Ultra Probeless Dry Ice monitor—a compact USB temperature datalogger that can be placed directly into dry ice environments as low as -95°C.

This new datalogger can be programmed with up to six temperature alarms, including trip duration. The integrated USB connector provides fast and easy download of data, and automatically generates a secure PDF report and encrypted data file when connected to a USB port on a PC. These files can be subsequently downloaded, viewed and archived in Sensitech's TempTale Manager® Desktop (TTMD) software or ColdStream® Cold Chain Manager private cloud database application. Furthermore, the TempTale Ultra Probeless Dry Ice monitor meets IATA's 2018 Dangerous Goods Regulations 59th Edition and thus requires no additional shipment labeling.

TempTale® Ultra Probeless Dry Ice Features


- Monitor temperatures as low as -95°C (-139°F)
- Place directly into dry ice environment in contact with product
- 3-Point NIST traceable calibration certificate accessible in TTMD or ColdStream software
- Large LCD screen provides clear indication of alarm status and trip statistics
- Program up to six alarms, including Trip Duration
- Flashing LEDs clearly indicate Start/Stop modes and Alarm status inside and outside of dry ice environments
- Download directly to PC via integrated USB connector
- Configurable PDF options such as, time zone, language and PDF/A file format
- Add shipment information prior to shipping to display on PDF report and in software when monitor is downloaded
- Write Protected flash drive for virus protection

TempTale Manager® Desktop Software

TempTale® Manager Desktop (TTMD) is a robust, multi-lingual, Windows-based software application used for configuring, downloading and archiving time and temperature data collected from TempTale temperature monitors. The power of TTMD software lies in its intuitive user interface that allows users to effortlessly analyze trip data in order to make high-quality shipment disposition decisions, and ensure that Standard Operating Procedures (SOPs) are delivering acceptable results.



Sample running display
Current temperature reading,
no alarm



Sample stopped display
Alarmed, total time above
high limit



ColdStream® Cold Chain Manager Software

ColdStream® Cold Chain Manager (CCM) is a validated, hosted and secure relational database application that is easily accessible via the Internet for query, reporting and analysis of stored data. ColdStream CCM provides centralized storage for time and temperature records in a secure, compliant repository. The hosted database application enables robust cold chain data analysis, reporting, and opportunities for process improvement.

TempTale® Ultra Probeless Dry Ice Specifications	
Monitoring Recording Options	Single Use, Single Use with User Programmable Overwrite
Operating Range	-95°C to +30°C (-139°F to +86°F)
Measurement Range	-90°C to +30°C (-130°F to +86°F)
Temperature Accuracy Range	±1.0°C from -90°C to +30°C (±1.8°F from -130°F to +86°F)
Temperature Resolution	0.1°C over full temperature measurement range
Data Storage Capacity	16,000 data points (16K)
Operating Life / Battery Type	<ul style="list-style-type: none"> • 30 days of continuous exposure to dry ice temperatures at or below -80°C • Two (2) TL-2450 3.6v coin cell lithium batteries—non-replaceable
Data Sampling Interval	Programmable from 30 seconds up to a maximum of 15 minutes in 30 second increments
Start Up Delay	0 minutes to 24 hours in 30 second increments
Programmable Alarms	<ul style="list-style-type: none"> • Programmable high and low limits → alarm is triggered when temperature exceeds set limits • Up to six alarms (single temperature limit, temperature range, dual temperature range, MKT, duration)
Alarm Delay Time Thresholds	Single event (continuous), cumulative
LCD Indicators	<ul style="list-style-type: none"> • Started, start-up delay, running, stopped • Alarm status: OK (✓), Alarmed (✗) • Trip summary data (average, minimum, maximum) • Current temperature reading • Time remaining / time elapsed against alarm thresholds • Total Time Above High/Low Alarm limits
LED Indicators	<ul style="list-style-type: none"> • Blinking Startup LED • Blinking Stop LED • File generation in process • Printer-ready mode activated for printing of PDF report to USB printer
Start Up Options	Manual push button or automatic launch option
Typical Dimensions	108mm L x 50.2mm W x 15.2mm H
Weight	Approximately 65 g (2.3 oz)
PDF Languages	English, German, French, Spanish, Chinese
PDF File Formats	PDF or PDF/A
IP Rating	IP64 (with silicon cap on)
Time Accuracy	± 5 minutes per month when exposed to temperatures at or above -90°C
Quality Assurance Certifications	<ul style="list-style-type: none"> • CE, RTCA – D0160G compliant, RoHS compliant, Response time tested to U.S. Pharmacopeia (USP) <1118> and EN 12830 standards • 3-point NIST® Traceable Certificate of Calibration • Validation Manual
Data Analysis Software	TempTale® Manager Desktop Software 8.3 or higher ColdStream® Cold Chain Manager Software 1.8B or higher
Minimum System Requirements	Windows PC w/ Windows 7 or higher; Adobe Reader 9.0 or higher
Computer Interface	USB 2.0, A-type plug
Ship Air in Accordance With	2018 IATA Dangerous Goods Regulations 59th Edition

Sensitech has performed all necessary testing and can provide documentation supporting our compliance at your request.

Sensitech Inc. is focused on delivering supply chain visibility solutions that track, monitor and protect products for global leaders in the food, life sciences, consumer goods, and industrial markets. Our solutions are focused in three key areas: quality and compliance, supply chain security, and logistics performance management. Quality and compliance solutions address temperature-sensitive, complex supply chains focused on delivering the highest quality possible, while our supply chain security solutions help to mitigate risks associated with theft, diversion and chain of custody. Sensitech's logistics performance solutions deliver origin-to-destination, real-time transparency to any in-transit journey. Sensitech Inc. is an ISO 9001:2008 company, headquartered in Beverly, Mass., with more than 35 sales, service and distribution locations around the world. Sensitech is a part of UTC Climate, Controls & Security, a unit of United Technologies Corp., a leading provider to the aerospace and building systems industries worldwide. Visit www.sensitech.com for additional information. © 2018 Sensitech Inc. All Rights Reserved. Unless otherwise indicated, all trademarks and service marks are the property of Sensitech Inc. NIST is a registered trademark of The National Institute of Standards and Technology Agency of the United States Government. Microsoft, Windows, Windows XP, Windows Vista, and Internet Explorer are registered trademarks of Microsoft Corporation in the United States and other countries. Adobe is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries.